

SEASPENSION® Pedestal User Information

Please read before installing or using SEASPENSION®

Bench Post Model 20xx

When installing the SEASPENSION® Bench Posts, you will note that both Posts have hinged top plates. One of the Posts has a hinged plate, which also slides within a slot, and the other Post has a hinged plate, which just hinges around a stationary point.

Space both Posts as far away as possible, keeping the proper distance of the Posts in accordance with the width of the bench to be mounted on. Position the stationary point hinged plated Post on the left (port), and position the sliding hinged slotted Post on the right (starboard). Make sure that the sliding slotted **top plate** is slid towards the starboard side, which would show the open area of the slot also towards the starboard side. This will allow for additional travel required when different loads are exerted on each Post, and keeps the Posts from binding. **On third (center mounted) Post installations, position the sliding plate with the hinge rod in the center of the slot. If equipped with wiring, DO NOT PULL ON THE WIRES, as they are pre-measured internally.**

Important: Ensure that the Posts are mounted with the plates square front to back and to each other. You can take diagonal measurements from one Post to the other, and the opposite measurement should be the same. Adjust accordingly. Always bolt the bases properly. We recommend thru bolting with 5/16"-18 stainless steel bolts with self locking nuts. Use a backing plate where possible. Consult a marine repair facility for further advise.

The SEASPENSION® Bench Posts are designed to operate independently. By following the above guidelines, no binding should occur when there are occupants of substantially different weights seated.

Note: Bench Posts can be ordered independently with either Standard or Heavy Duty springs.

Maintenance

After use, wash Post with fresh water and mild soap. Posts can be wiped down with a Teflon or silicon spray. A rubber preservative is recommended (303 Aerospace Protectant) for the EPDM boot. Please call to order. Periodically check the Post, locks, and bolts for signs of wear. Contact your local Dealer or the factory if you have any questions concerning SEASPENSION®.

IMPORTANT NOTICE: Each pedestal is designed for a total seated weight of 275 Lbs. This means occupant and seat weight combined. We recommend seats of less than 35 Lbs per pedestal application. If you opt for a larger and/or heavier seat or applications, we recommend an additional pedestal. Call the factory for more information. If excessive play or wobbling is experienced, ***discontinue use*** and consult the factory. Use common sense!

Thank you for purchasing SEASPENSION® and remember,

Sit Down & Enjoy The Ride !

Manufactured by Seaspension Technologies, Inc.
11683 87th Street N., Largo, FL 33773. Phone: 727-216-9639 Fax: 727-388-6934

