

SEASPENSION® Pedestal User Information

Please read before installing or using **SEASPENSION®**

Spider Post Model 30xx and Non-Swivel Model 40xx

Alignment orientation should be with the top bolts (inside the spider top or on the top of the non-swivel plate) in a left & right (3 o'clock-9 o'clock) position if at all possible.

We recommend that all the Posts be thru bolted with 5/16"-18 stainless steel bolts and self-locking nuts. Use a backing plate where possible. Bolt holes may not line up with holes from previous pedestal installations due to the orient specific nature of some **SEASPENSION®** Posts (model 40xx). Actual installation is similar to most other pedestal installation. Consult your marine repair facility for further advice.

Maintenance

After use, wash Post with fresh water and mild soap. Posts can be wiped down with a Teflon or silicon spray. A rubber preservative is recommended (303 Aerospace Protectant) for the EPDM boot. Please call to order. Periodically check the Post, nuts and bolts for signs of wear. Contact your local Dealer or the factory if you have any questions concerning **SEASPENSION®**

IMPORTANT NOTICE: each pedestal is designed for a total seated weight of 275 Lbs. This means occupant and seat weight combined. We recommend seats of less than 35 Lbs per pedestal application. If you opt for a larger and/or heavier seat or application, we recommend an additional pedestal. Call the factory for more information. If excessive play or wobbling is experienced, *discontinue use* and consult the factory. Use common sense!

Thank you for purchasing **SEASPENSION®** and remember,

Sit Down & Enjoy The Ride!

Manufactured by Seaspension Technologies, Inc.

11683 87th St. N., Largo, 33773. Phone: 727-216-9639 Fax: 727-388-6934